

BWT2 TOP



FEATURES

- ✓ Filter manufactured with GRP through continuous bobbin winding technology.
- ✓ Excellent finish.
- ✓ Colour: Ral 6027.
- ✓ Filter for a Top multiport valve.
- ✓ Water and air drain of ¼".
- ✓ Models 1050, 1200 with 2 ½" sand drain.
- ✓ Maximum pressure: 2.5 bar.
- ✓ Maximum temperature: 50°C.
- ✓ Fitted with 1" laterals


CARACTERÍSTICAS

- ✓ Filtros fabricados con bobinado continuo de poliéster y fibra de vidrio.
- ✓ Excelente acabado.
- ✓ Color: Ral 6027.
- ✓ Filtro para válvula Top.
- ✓ Purga de agua y aire de ¼".
- ✓ Modelos 1050, 1200 con descarga de arena 2 ½".
- ✓ Presión máxima de 2.5 bar.
- ✓ Temperatura máxima: 50°C.
- ✓ Equipado con brazos colectores de 1"

FILTER DETAILS



- Models 1050, 1200 with 2 ½" sand drain
- Descarga de arena 2 ½" en modelos 1050, 1200



- Fitted with 1" laterals
- Equipado con brazos colectores 1"



- Multiport Top valve

Code	Model (mm)	Connections (mm/inch)		Filtering velocity (m ³ /h/m ²)	Flow (m ³ /h)	Maximum pressure (bar)	Sand (0.4-0.8mm) (kg)	Gravel (1-2mm)	Net weight (kg)	D (mm)	H (mm)	M (mm)	N (mm)
		mm	inch										
66243CL96N	400	50	1 ½"	50	6.5	2.5	60	-	10	420	910	670	735
66244CL96N	500	50	1 ½"	50	9.5	2.5	100	-	15	520	960	715	780
66245CL96N	600	50	1 ½"	50	15	2.5	160	-	20	620	1030	790	855
71274CL96N	660	50	1 ½"	50	17	2.5	210	-	27	674	1134	845	910
66246CL96N	750	63	2"	50	21	2.5	290	-	33	780	1180	815	895
66247CL96N	900	63	2"	50	32	2.5	500	-	51	930	1320	1035	1115
70721CL96N	1050	63	2"	50	43	2.5	550	250	65	1070	1180	815	895
70722CL96N	1200	63	2"	50	56	2.5	750	300	90	1220	1320	1035	1115

Code	Box MPV (cm)	Box filter (cm)	Units per pallet
66243CL96N	22x22x39	43x43x71	15
66244CL96N	22x22x39	54x54x75	10
66245CL96N	22x22x39	63x63x86	8
71274CL96N	22x22x39	63x63x89	8
66246CL96N	27x24x44	80x80x93	2
66247CL96N	27x24x44	96x96x110	2
70721CL96N	27x24x44	124x124x170	1
70722CL96N	27x24x44	135x135x185	1

